## **SENATE BILL 713**

R6

Slr2684

CF HB 1168

By: Senators Astle, Brinkley, Colburn, DeGrange, Della, Garagiola, Haines,

Kramer, Munson, Stoltzfus, and Stone, and Jacobs

Introduced and read first time: February 1, 2008

Assigned to: Judicial Proceedings

Committee Report: Favorable with amendments

Senate action: Adopted

Read second time: March 11, 2008

CHAPTER

			_
1	$\Lambda \Lambda T$	$\Lambda CT$	concerning
ı	AIN	$\mathbf{A} \mathbf{U} \cdot \mathbf{I}$	concerning

## 2 Vehicle Laws - Equipment on Motorcycles - Auxiliary Lighting

- FOR the purpose of authorizing the use of certain auxiliary lighting on a motorcycle; and generally relating to motorcycle lighting.
- 5 BY repealing and reenacting, with amendments, adding to
- 6 Article Transportation
- 7 Section <del>22-224.1</del> <u>22-221(1)</u>
- 8 Annotated Code of Maryland
- 9 (2006 Replacement Volume and 2007 Supplement)
- 10 SECTION 1. BE IT ENACTED BY THE GENERAL ASSEMBLY OF
- 11 MARYLAND, That the Laws of Maryland read as follows:

## **Article – Transportation**

13 <del>22 224.1.</del>

12

- 14 (a) In this section, "motorcycle" includes Class M (multipurpose) vehicles
  15 that are designated by the Administrator.
- 16 (b) The headlamp or headlamps on a motorcycle may be of the single-beam 17 or multiple-beam type, but in either event shall comply with the following

18 requirements and limitations:

## EXPLANATION: CAPITALS INDICATE MATTER ADDED TO EXISTING LAW.

[Brackets] indicate matter deleted from existing law.

<u>Underlining</u> indicates amendments to bill.

Strike out indicates matter stricken from the bill by amendment or deleted from the law by amendment.



1	(1) The headlamp or headlamps on a motorcycle shall be of sufficien
2	intensity to reveal a person or a vehicle at a distance of:
3	(i) Not less than 100 feet, when the motorcycle is operated a
4	any speed of less than 25 miles an hour;
_	(") Net leastless 200 feet also set as also see
5 6	(ii) Not less than 200 feet, when the motorcycle is operated at a speed of 25 to 34 miles an hour; and
O	speed of 25 to 54 linnes an nour, and
7	(iii) Not less than 300 feet, when the motorcycle is operated at a
8	speed of 35 miles an hour or more;
9	(2) If the motorcycle is equipped with a multiple-beam headlamp of
10	headlamps, the upper beam shall meet the minimum requirements set forth above and
11	may not exceed the limitations set forth in § 22–222(a)(1) of this subtitle, and the
12	lowermost beam shall meet the requirements applicable to a lowermost distribution o
13	light as set forth in § 22–222(a)(2) of this subtitle; and
14	(3) If the motorcycle is equipped with a single-beam lamp or lamps
1 <del>4</del> 15	(3) If the motorcycle is equipped with a single-beam lamp or lamps the lamp or lamps shall be so aimed that, when the vehicle is loaded, none of the
16	high-intensity portion of light, at a distance of 25 feet ahead, projects higher than the
17	level of the center of the lamp from which it comes.
-•	level of the contest of the famp from which it contest
18	(C) THIS SECTION DOES NOT PROHIBIT THE USE OF THE FOLLOWING
19	NONFLASHING AUXILIARY LIGHTING ON A MOTORCYCLE:
20	(1) Blue DOT ILLUMINATION;
21	(2) STANDARD BULB RUNNING LIGHTS; OR
	· · · · · · · · · · · · · · · · · · ·
22	(3) LIGHT-EMITTING DIODE PODS AND STRIPS ADDED TO
23	PROTECT THE DRIVER.
24	<u>22–221.</u>
25	(L) (1) SUBJECT TO PARAGRAPH (2) OF THIS SUBSECTION, A
26	MOTORCYCLE MAY BE EQUIPPED WITH THE FOLLOWING AUXILIARY LIGHTING:
27	(I) BLUE DOT ILLUMINATION;
28	(II) STANDARD BULB RUNNING LIGHTS; OR
29	(III) LIGHT-EMITTING DIODE PODS AND STRIPS ADDED TO
30	PROTECT THE DRIVER.
-	
31	(2) (I) LIGHTING UNDER THIS SUBSECTION SHALL BE:

1		<u>1.</u>	Nonblinking;
2		<u>2.</u>	Nonflashing;
3		<u>3.</u>	Nonoscillating; and
4 5	TRAIN OF THE MOTOR	4. CYCLE	DIRECTED TOWARD THE ENGINE AND THE DRIVE
6	<u>(II)</u>	<u>Ligi</u>	HTING UNDER THIS SUBSECTION MAY NOT:
7 8	MOTORCYCLE; OR	<u>1.</u>	BE ATTACHED TO THE WHEELS OF THE
9		<u>2.</u>	EMIT A RED OR BLUE LIGHT.
10	<u>(III)</u>	BLU	E DOT ILLUMINATION:
11 12	MOTORCYCLE AS PAR	<u>1.</u> T OF O	MAY BE LOCATED ONLY ON THE REAR OF A R ADJACENT TO THE REAR BRAKE LIGHT; AND
13 14	IN DIAMETER.	<u>2.</u>	MAY NOT EXCEED THREE-QUARTERS OF AN INCH
15 16	SECTION 2. AN June 1, 2008.	D BE I'	T FURTHER ENACTED, That this Act shall take effect
	Approved:		
			Governor.
			President of the Senate.
			Speaker of the House of Delegates.